

BI-FOLD DOORS ENQUIRY/ORDER FORM

Company: _____
 Account no: _____
 Address: _____

 Postcode: _____
 Tel: _____
 Fax: _____
 Contact Name: _____
 Email: _____

Requested Delivery Date: _____
 Order Reference: _____
 Signature: _____

Page of

Quote

Order

Any glazing or part of that glazing, which is between the finished floor level and a height of 800m requires toughened glass as per BS 6262 Part 4: 1994. Ref Part N Building Regulations 1991.

Additional notes: _____

Frame colour

White
 Rosewood
 Rosewood on White
 Golden Oak
 Golden Oak on White
 Mahogany
 Mahogany on White

Hardware options

White Gold
 Black Chrome

Sigenia hinge covers

White Brown

Top & bottom track

White Brown

Dimensions (Excluding extension)

Overall width: _____

Overall height: _____

Maximum height: 2380mm

Frame extension

25mm frame extension: _____

x 2.5 mtr = Qty.

Open in/out

Open in
 Open out

Glazing (28mm only)

Toughened clear
 Unglazed

U-value

1.2 Energy efficient (A)
 2.0 Lower Cost spec. (B) (STD)

Sill type (Aluminium only)

Track trim
 85mm
 150mm

Trickle vent

Required

Folding options (When viewed from outside)

.....
Total number of leaves	Number of leaves folding left	Number of leaves folding right

For example:

3	1	2
<i>Total number of door leaves</i>	<i>Number of door leaves opening left</i>	<i>Number of door leaves opening right</i>

Glazing (28mm only)

Chamfered Sculptured

Trickle vent will be fitted into 25mm frame extender on the top

DOOR OPENS IN 150mm Sill Nose

DOOR OPENS OUT 150mm Sill Nose

